

**Table 1**  
Bicycle Compatible  
Roadway Pavement  
Widths

**Condition I**  
**AADT 1200\* -2000**

	URBAN W/PARKING	URBAN W/O PARKING	RURAL
<50 km/h (30 mph)	SL 3.6m (12 ft.)	SL 3.3m (11 ft.)	SL 3.0m (10 ft.)
50 km/h-65 km/h (31-40 mph)	SL 4.2m (14 ft.)	SL 4.2m (14 ft.)	SL 3.6m (12 ft.)
65 km/h-80 km/h (41-50 mph)	SL 4.5m (15 ft.)	SL 4.5m (15 ft.)	SH 0.9m (3 ft.)
>80 km/h (50 mph)	NA	SH 1.2m (4 ft.)	SH 1.2m (4 ft.)

\* For volumes less than 1200 a shared lane is acceptable.

KEY: SH=shoulder SL=shared lane

**Condition II**  
**AADT 2000-10,000**

	URBAN W/PARKING	URBAN W/O PARKING	RURAL
<50 km/h (30 mph)	SL 4.2m (14 ft.)	SL 3.6m (12 ft.)	SL 3.6m (12 ft.)
50 km/h-65 km/h (31-40 mph)	SL 4.2m (14 ft.)	SL 4.2m (14 ft.)	SH 0.9m (3 ft.)
65 km/h-80 km/h (41-50 mph)	SL 4.5m (15 ft.)	SL 4.5m (15 ft.)	SH 1.2m (4 ft.)
>80 km/h 50 mph	NA	SH 1.8m (6 ft.)	SH 1.8m (6 ft.)

**Condition III**  
**AADT over 10,000 or Trucks over 5%**

	URBAN W/PARKING	URBAN W/O PARKING	RURAL
<50 km/h (30 mph)	SL 4.2m (14 ft.)	SL 4.2m (14 ft.)	SL 4.2m (14 ft.)
50 km/h-65 km/h (31-40 mph)	SL 4.2m (14 ft.)	SH 1.2m (4 ft.)	SH 1.2m (4 ft.)
65 km/h-80 km/h (41-50 mph)	SL 4.5m (15 ft.)	SH 1.8m (6 ft.)	SH 1.8m (6 ft.)
>80 km/h (50 mph)	NA	SH 1.8m (6 ft.)	SH 1.8m (6 ft.)

**NOTE:** NJDOT minimum shoulder width of 2.4 meters (8 feet) should be provided wherever possible on roadways having an AADT greater than 10,000 vehicles.

