



TOWNSHIP of HOPEWELL MERCER COUNTY

**201 WASHINGTON CROSSING – PENNINGTON ROAD
TITUSVILLE, NEW JERSEY 08560-1410**

PROJECT / APPLICATION

BLOCK:


LOT:





ADDRESS:


PROJECT NAME:

PLANS

Part 12 - Construction Details









CLEANOUT RISER COVER DETAIL

NOT TO SCALE



DEPRESSED WATERLINE

NOT TO SCALE




ROOF DRAIN CLEANOUT DETAIL

NOT TO SCALE


WATER MAIN TRENCH DETAIL

NOT TO SCALE



SEWER PUMP STATION LAYOUT

NOT TO SCALE



PIPE/WALL JOINT DETAIL

N.T.S.

STORM INLET & MANHOLE NOTES

- Corbeling of inlet walls will be permitted at the rate of 1/2" per 8' of height of wall; maximum corbel 6" per wall.
- When the item manholes, inlets and catch basins, additional depth is scheduled in the proposal and the depth of a structure exceeds 10' as measured from top of cover or grate to invert of drainage structure, the walls of the structure below a depth of 8' shall be 12" thick, and the overall horizontal dimensions of foundations shall be increased 12", and except in rock the depth increased to 12".
- Except for catch basins and type A inlets, footings and invert shall be constructed in two stages, and the bottom of the footings shall be 8" below the outer wall of the lowest pipe in inlets and 10" in manholes.
- Ladder rungs of precast inlets shall be spaced a maximum of 18".
- Inlets shall be built with a precast shaft placed on a 6" thick bed of compacted coarse aggregate, 57% fine aggregate shall extend 6" beyond the horizontal limits of the inlet foundation.
- Castings for precast inlets and manholes shall be adjusted to grade with courses of brick, as required, 12" maximum. 6" min. shall be allowed for in precast design.
- When the depth of a precast inlet exceeds 10' as measured from top of grate to invert, the foundation shall be increased to 12", when rock is encountered the depth of the foundation shall not be increased.
- Minimum wall reinforcement for precast inlets type A, B, C, E, D-1 and B modified.

DEPTH BELOW TOP OF GRADE	HORIZONTAL REINFORCEMENT	VERTICAL REINFORCEMENT	WALL THICKNESS
0' TO 10'-0"	#4 @ 18" C.C.	#4 @ 18" C.C.	6"
10'-1" TO 15'-0"	#4 @ 8" C.C.	#4 @ 18" C.C.	6"
15'-1" TO 20'-0"	#4 @ 6" C.C.	#4 @ 18" C.C.	6"


REINFORCING FOR PRECAST INLETS IS THE MINIMUM REQUIRED. ADDITIONAL REINFORCING FOR HANDLING IS THE RESPONSIBILITY OF THE CONTRACTOR.

- The item of reset heads shall include raising or lowering the head castings of inlets and catch basins, or the raising of manhole head castings, for a maximum of 12". All other changes in position of head casting shall be considered as reconstructed manholes or reconstructed inlets or catch basins.

- When curb piece height specified is greater than curb face height, depress the gutter of grate so that the top of curb piece is at the same elevation as the top of curb.


STORM PRECAST MANHOLE

NOT TO SCALE



PIPE TRENCH DETAIL - RCP PIPE


NOT TO SCALE



PIPE TRENCH DETAIL - H.D.P.E. PIPE


NOT TO SCALE

- Foundation where the trench bottom is unstable, the contractor shall excavate to a depth required by the engineer and stabilize the bottom of the trench with a suitable material for installation of thermoplastic pipe for sewers another gravity-flow applications. LATEST EDITION. AS AN ALTERNATIVE AND AT THE DISCRETION OF THE ENGINEER, THE TRENCH BOTTOM MAY BE STABILIZED USING A WOVEN GEOTEXTILE FABRIC.
- Bedding: suitable material shall be class I, II, or III and installed as required in ASTM D2321, LATEST EDITION. UNLESS OTHERWISE SPECIFIED BY THE ENGINEER, MINIMUM BEDDING THICKNESS SHALL BE 4" FOR 4" TO 24" AND 42" TO 48" CORRUGATED POLYETHYLENE PIPE AND 6" FOR 30 TO 26" CPE.
- Haunching and initial backfill: suitable material shall be class I, II, or III and installed as required in ASTM D2321, LATEST EDITION.



INLET TYPE "B" DETAIL WITH C.I. CURB PIECE-BACK-FRAME AND GRATE

NOT TO SCALE



INLET TYPE "E"

NOT TO SCALE

THESE PLANS ARE NOT TO BE USED FOR BID OR CONSTRUCTION


CONSTRUCTION DETAILS-UTILITY
THE COLLECTION at HOPEWELL
BLOCK 85, LOT 3, BLOCK 86, LOTS 32-34 & PART OF BLOCK 85, LOT 9
TOWNSHIP OF HOPEWELL, MERCER COUNTY, NEW JERSEY

PRELIMINARY & FINAL MAJOR SUBDIVISION AND FINAL SITE PLAN
SHEET No. 16
A

Bowman
CONSULTING

6/20/16 0809-0-1-0401	CHG 0200
THIS DRAWING AND ALL INFORMATION CONTAINED THEREIN ARE THE PROPERTY OF BOWMAN CONSULTING GROUP, INC. USE OR REPRODUCTION BY ANYONE OTHER THAN THE CONTRACTOR IS PROHIBITED UNLESS EXPRESSLY AUTHORIZED IN WRITING BY BOWMAN CONSULTING GROUP, INC.	4
THE DRAWING AND ALL INFORMATION CONTAINED THEREIN ARE THE PROPERTY OF BOWMAN CONSULTING GROUP, INC. USE OR REPRODUCTION BY ANYONE OTHER THAN THE CONTRACTOR IS PROHIBITED UNLESS EXPRESSLY AUTHORIZED IN WRITING BY BOWMAN CONSULTING GROUP, INC.	3
THIS DRAWING AND ALL INFORMATION CONTAINED THEREIN ARE THE PROPERTY OF BOWMAN CONSULTING GROUP, INC. USE OR REPRODUCTION BY ANYONE OTHER THAN THE CONTRACTOR IS PROHIBITED UNLESS EXPRESSLY AUTHORIZED IN WRITING BY BOWMAN CONSULTING GROUP, INC.	2
THIS DRAWING AND ALL INFORMATION CONTAINED THEREIN ARE THE PROPERTY OF BOWMAN CONSULTING GROUP, INC. USE OR REPRODUCTION BY ANYONE OTHER THAN THE CONTRACTOR IS PROHIBITED UNLESS EXPRESSLY AUTHORIZED IN WRITING BY BOWMAN CONSULTING GROUP, INC.	1


Phone: 732-465-5500
Fax: 732-465-5601
NJ Certificate of Authorization No. 240-2020
www.bowmanconsulting.com
Email: info@bowmanconsulting.com



NOTE: Foreman must note on this plan the location of any alterations (withdrawals, substitutions, or additions to the listed materials used in this project.)


STANDARD METER SETUP DETAIL

NOT TO SCALE




FIRE PREVENTION & METERING DETAIL

NOT TO SCALE




FIRE PREVENTION & METERING DETAIL

NOT TO SCALE




FIRE PREVENTION & METERING DETAIL

NOT TO SCALE




STORM/ SANITARY INSTALLATION AROUND WATER MAIN

NOT TO SCALE




FIRE PREVENTION & METERING DETAIL

NOT TO SCALE




FIRE PREVENTION & METERING DETAIL

NOT TO SCALE




Typical Water Main Casing Detail

NOT TO SCALE





OFFSET AROUND OBSTRUCTION

NOT TO SCALE



METER SETUP REQUIREMENTS

Page 19 of 26



CONCRETE THRUST BLOCK DETAIL

NOT TO SCALE

GENERAL PLANTING NOTES

PLANTING

1. THE PLANTING PLAN SHALL BE USED FOR LANDSCAPE PLANTING PURPOSES ONLY. EXAMINE ALL ENGINEERING DRAWINGS AND FIELD CONDITIONS FOR SPECIFIC LOCATIONS OF UTILITIES, STRUCTURES, ETC. AND NOTIFY THE LANDSCAPE ARCHITECT IN REFERENCE TO ANY DISCREPANCIES OR LOCATION CONFLICTS PRIOR TO PLANTING.

2. THE CONTRACTOR SHALL ENSURE THAT WORK THAT DOES NOT INTERRUPT ESTABLISHED OR PROJECTED DRAINAGE PATTERNS.

3. IN THE EVENT OF VARIATIONS IN PLANTED QUANTITIES AND QUANTITIES SHOWN ON THE PLAN, THE PLANTING PLAN PRECEDENCE, THE CONTRACTOR IS RESPONSIBLE FOR VERIFYING ALL PLANT QUANTITIES PRIOR TO THE COMMENCEMENT OF WORK. SOD AND SEED QUANTITY TAKE-OFFS ARE THE RESPONSIBILITY OF THE CONTRACTOR. ALL DISCREPANCIES SHALL BE REPORTED TO THE LANDSCAPE ARCHITECT FOR APPROVAL PRIOR TO PLANTING. THE CONTRACTOR SHALL FURNISH PLANT MATERIAL IN SIZES AS SPECIFIED IN PLANT LISTS.

4. PLANTS SHALL BE LOCATED AS SHOWN ON THE DRAWINGS OR UNLESS OTHERWISE NOTED.

5. ALL PLANT MATERIAL SHALL CONFORM TO CURRENT AMERICAN STANDARDS FOR LUMBER STOCK BY AMERICAN LUMBER INSTITUTE. ALL PLANT MATERIAL SHALL BE FREE OF DISEASE, SUBSTANTIALLY UNIFORM IN SIZE AND SHAPE AND HAVE STRAIGHT TRUNKS.

6. ALL PLANTS (BAG OR CONTAINER) SHALL BE PROPERLY IDENTIFIED BY WEATHERPROOF LABELS SECURELY ATTACHED TO THE PLANT. PLANT MATERIAL IN BAGS OR CONTAINERS SHALL NOT BE REMOVED UNTIL THE FINAL INSPECTION BY THE LANDSCAPE ARCHITECT OR OWNER'S REPRESENTATIVE AND TOWNSHIP ENGINEER.

7. ALL PLANTS SHALL BE PLANTED BY THE LANDSCAPE ARCHITECT, OWNERS' REPRESENTATIVE, OR TOWNSHIP ENGINEER IF IT DOES NOT MEET THE REQUIREMENTS OF THE SPECIFICATIONS. ALL REJECTED MATERIALS SHALL BE REMOVED FROM THE SITE BY THE CONTRACTOR.

8. PLANT SUBSTITUTIONS SHALL BE PERMITTED ONLY WITH WRITTEN CONSENT OF THE OWNER OR LANDSCAPE ARCHITECT. PLANT MATERIALS SUBSTITUTED SHALL BE OF EQUIVALENT SIZE, VARIETY, AND SHAPE. PLANT MATERIALS SHALL BE TO TRUE SPECIES, VARIETY, AND SIZE AND BE CERTIFIED DISEASE AND INSECT FREE. WRITTEN PROOF OF UNAVAILABILITY OF PLANT MATERIAL, MUST BE DOCUMENTED.

9. ALL PLANT MATERIALS SHALL BE PLANTED ON ENTIRELY OUT OF PLANTING BEDS. PLANTING BED LINES ARE NOT TO BE OBSTRUCTED. ALL SHRUBS AND GROUND COVER AREAS SHALL BE PLANTED IN CONTINUOUS PREPARED BED AND TOP DRESSED WITH A 3 INCH LAYER OF SHREDDED HARDWOOD MULCH. MULCH SHALL HAVE BEEN SHREDDED WITHIN THE LAST SIX MONTHS.

LAWN SOD SPECIFICATIONS:

1. THE SOD COMPOSITION SHALL BE AS FOLLOWS:

80% TALL FESCUE
20% KENTUCKY BLUEGRASS

2. THE SOD SHALL BE OF GOOD TEXTURE, FREE FROM OBNOXIOUS ROOTS, STONES, AND FOREIGN MATERIAL. SOD SHALL BE FRESH CULTIVATED, PLANTED, WELDED, AND FRESHLY-CUT.

3. THE SOD SHALL BE OBTAINED FROM AREAS HAVING GROWING CONDITIONS SIMILAR TO AREAS BEING COVERED. SOD SHALL HAVE A CLEAN GROWTH OF ACCEPTABLE GRASS AND SHALL BE MACHINE CUT WITH NOT LESS THAN 1" LOAMY SAN FIRMLY ADHERING TO THE ROOTS.

4. INDIVIDUAL PIECES OF SOD SHALL BE CUT TO THE SUPPLIER'S STANDARD WIDTHS AND LENGTH IF GREATER THAN 5% OF SOD PIECES HAS BROKEN PADS OR TORN OR UNEVEN EDGES, IT WILL NOT BE ACCEPTED.

5. STANDARD SIZE SECTIONS OF SOD SHALL BE STRONG ENOUGH TO SUPPORT THEIR OWN WEIGHT AND RETAIN THEIR SHAPE UNDISTURBED AND UNCOMPACTED FROM A FIRM GRASP ON THE UPPER 1/3 OF THE SECTIONS.


6. SOD SHALL NOT BE HARVESTED OR TRANSPORTED UNDER DROUGHT CONDITIONS. IF THE SOIL IS DRY, SOD SHALL BE WATERED SUFFICIENTLY TO MOISTEN THE SOD TO A DEPTH AT WHICH THE SOIL IS TO BE CUT.

7. DUMPING PLANT TRAILERS OR VEHICLE WILL NOT BE PERMITTED. DUMPING PLANT THAT HAS TURNED YELLOW IN COLOR WILL BE REJECTED. SOD SHALL BE INSPECTED AT THE TIME OF DELIVERY BY THE LANDSCAPE ARCHITECT AND/OR OWNER'S REPRESENTATIVE AND ANY SOD THAT DOES NOT MEET THE SPECIFICATIONS WILL BE REJECTED AND REMOVED FROM THE JOB SITE AT THE CONTRACTOR'S EXPENSE.


8. SOD SHALL BE HARVESTED, DELIVERED AND INSTALLED WITHIN A PERIOD OF 36 HOURS. HOWEVER, IF HIGH TEMPERATURE AND LOW MOISTURE EXTREMES OCCUR, INSTALLATIONS SHOULD OCCUR WITHIN 24 HOURS OF HARVEST. SOD NOT TRANSPLANTED WITHIN THESE TIME PERIODS SHALL BE REMOVED FROM THE JOB SITE AT THE CONTRACTOR'S EXPENSE.

SHRUB PLANTING

NOT TO SCALE



PLAN



LAWN SEED MIXTURE:

	LBS. PER ACRE	LBS. PER 1,000 SF	OPTIMUM SEED DATE	ACCEPTABLE SEED DATE
HARD FESCUE	130	3		
CHESTNUT FESCUE	45	1		
STRONG CREEPING RED FESCUE	45	1	8/15 - 10/15	3/1 - 4/30 *
PERENNIAL RYEGRASS	10	0.25	5/1 - 8/14	

*Summer seedings should only be conducted when the site is irrigated. Mixes including white clover require that at least six weeks of growing season remain after seeding to ensure establishment before freezing conditions.

STORMWATER MANAGEMENT SEED MIXTURE - ERNMX-126

Botanical Name

Deergrass, Tioga
Alkaligrass, Fults
Virginia Wildrye, 'Madison'
Agrostis stolonifera
Poa palustris
Carex vulpinoidea, PA Ecotype
Carex scoparia, PA Ecotype
Fowl Bluegrass
Fox Sedge, PA Ecotype
Blunt Broom Sedge, PA Ecotype
Soft Rush

Common Name

Deergrass, Tioga

Alkaligrass, Fults

Virginia Wildrye, 'Madison'

Creeping Bentgrass

Fowl Bluegrass

Fox Sedge, PA Ecotype

Blunt Broom Sedge, PA Ecotype

Soft Rush

Optimum Seed Date

3/1 - 4/30 *

5/1 - 8/14

Acceptable Seed Date

Seeding Rate:

20-40 lbs per acre